

Make it easy
ISEKI



TG SERIES 35 - 47HP

ISEKI

MODEL			TG6370P.4R ROPS	TG6400H.4R ROPS	TG6400H.4C CAB	TG6490H.4C CAB	TG6490P.4R ROPS	TG6490P.4C CAB
Output Engine	Rated (Gross)	kW (HP)	26.6 (35.7) Iseki E3CG	28.7 (38.5) Iseki E3CDT	28.7 (38.5) Iseki E3CDT	35.1 (47.1) Iseki E4CG	35.1 (47.1) Iseki E4CG	35.1 (47.1) Iseki E4CG
Number of Cylinders			3	3	3	4	4	4
Displacement		litres	1.647	1.498	1.498	2.197	2.197	2.197
Fuel Tank		litres	40	40	40	53	53	53
DRIVE TRAIN								
Clutch Type			Dry Single STD	N/A STD	N/A STD	N/A STD	Dry Single STD	Dry Single STD
Transmission	Shuttle Main Sub		4 3	Servo HST 3	Servo HST 3	Servo HST 3 x 2 (Hi-Lo)	4 3	4 3
Gear Speeds			F12/R12	3	3	3 x 2	F12/R12	F12/R12
PTO								
Clutch Type			Independent	Independent	Independent	Independent	Independent	Independent
Rear PTO			540	540	540	540	540	540
REAR AXLE								
Diff-lock			STD	STD	STD	STD	STD	STD
Brake system			Wet disc	Wet disc	Wet disc	Wet disc	Wet disc	Wet disc
Parking brake			Lever Type	Lever Type	Lever Type	Lever Type	Lever Type	Lever Type
WHEEL & TYRE OPTIONS								
Tread Pattern			Turf Ag Industrial	Turf Ag Industrial	Turf Ag Industrial	Turf Ag Industrial	Turf Ag Industrial	Turf Ag Industrial
FRONT AXLE								
Drive Type			4WD	4WD	4WD	4WD	4WD	4WD
Steering System			Power steering	Power steering	Power steering	Power steering	Power steering	Power steering
Tilt steering			STD	STD	STD	STD	STD	STD
HYDRAULICS								
Lift Capacity	at link end	kg	1270	1270	1270	1580	1580	1580
	at 24" behind	kg	1150	1150	1150	1400	1400	1400
Pump Capacity		litres/min	74.3	74.3	74.3	74.3	74.3	74.3
Position control			STD	STD	STD	STD	STD	STD
Joy-stick			STD	STD	STD	STD	STD	STD
Hydraulic Outlet Valves @ Rear:			STD (Max)	2 (2)	2 (2)	2 (2)	2 (2)	2 (2)
3 POINT LINKAGE								
Category			I	I	I	I	I	I
Lift Rod Adjustment (RHS)			Turnbuckle	Turnbuckle	Turnbuckle	Turnbuckle	Turnbuckle	Turnbuckle
Check Chain			Turnbuckle	Turnbuckle	Turnbuckle	Turnbuckle	Turnbuckle	Turnbuckle
Lower Linkage end			Hook end	Hook end	Hook end	Hook end	Hook end	Hook end
Clevis			STD	STD	STD	STD	STD	STD
ELECTRICAL								
Battery			12V 55Ah 582A	12V 55Ah 582A	12V 55Ah 582A	12V 72Ah 600A	12V 72Ah 600A	12V 72Ah 600A
Digital panel			STD	STD	STD	STD	STD	STD
DIMENSIONS								
Overall Length		mm	3,070	3,070	3,070	3,370	3,370	3,370
Overall Width		mm	1,545	1,545	1,545	1,810	1,810	1,810
Overall Height		mm	2,180	2,570	2,275	2,325	2,300	2,325
Wheel Base		mm	1,770	1,770	1,770	1,900	1,900	1,900
Shipping Weight		kg	1,375	1,385	1,535	1,870	1,545	1,715

Specifications, standard and optional equipment on products change from time to time. Please consult your local dealer to ensure your expectations are matched by the product which will be available locally at the time you take delivery.